

# AE 402 Indicator



## Features

- Large backlit LCD
- Colour coded keys
- Rechargeable Battery
- Bi-directional RS-232 interface
- Bracket for wall mounting
- Hold function
- Grade 304 stainless steel housing
- Check weighing LED lights
- Capacity tracker
- Wash down meets IP66 standards

## Applications

- Weighing
- Check weighing
- Parts counting
- Animal / dynamic weighing
- Percentage weighing

## Accessories

- No.700000012 Adam Printer
- No.400005054 Thermal Printer Paper
- No.600002028 AdamDU data collection software
- No.3074010266 RS-232-USB cable

## Technical Specifications

<b>Model</b>	<b>AE 402</b>
<b>Capacity</b>	Selectable from 1.5kg to 750,000kg
<b>Readability</b>	Selectable from 0.0001kg to 50kg
<b>Resolution</b>	Up to 1:15,000

## General Specifications

<b>Units of measurement</b>	Gram (g), Kilogram (kg), Pound (lb), Ounce (oz), Pound/Ounce (lbs/oz), Newtons
<b>Excitation</b>	5Vdc
<b>Sensitivity</b>	0.15uv/d
<b>Linearity</b>	0.01% FS
<b>Zero Range</b>	0- 10mv
<b>Signal Range</b>	0-40mv
<b>Number of Loadcell</b>	Up to 4 loadcells 350 ohms - Minimum 87 ohms - Maximum 1120 ohms
<b>Typical stabilisation time</b>	2-3 Secs
<b>Interface</b>	Bi-directional RS-232 (Standard)
<b>Calibration</b>	Automatic External
<b>Display</b>	6 digit LCD - green backlit with 40mm digits
<b>Power supply</b>	Mains Power Cord / Rechargeable Battery
<b>Connection</b>	4 wires - 2 Excitation, 2 signals
<b>Housing</b>	SS Grade 304 - IP66
<b>Overall dimension (wxdxh)</b>	240mm x 145mm x 95mm
<b>Net Weight</b>	2kg

