

GFK and GFK-M Floor Check Weighing Scales



Technical Specifications

Model	GFK 75	GFK 150	GFK 300	GFK 600	GFK 75H	GFK 150H
Maximum capacity	75kg	150kg	300kg	600kg	75kg	150kg
Readability	5g	10g	20g	50g	1g	2g
Repeatability (S.D.)	5g	10g	20g	50g	2g	4g
Linearity (±)	10g	20g	40g	100g	3g	6g
Pan size	400mm x 500mm		600mm x 800mm		400mm x 500mm	

EC Type Approved Models:

Model	GFK 60M	GFK 150M	GFK 300M
Maximum capacity	60kg	150kg	300kg
Readability	20g	50g	100g
Pan size	400mm x 500mm		

General Specifications

Units of measurement	GFK 75-GFK 600: Gram (g), Kilogram (kg), GFK 60M-300M: Kilograms (kg)
Typical stabilisation time	2-3 Secs
Interface	RS-232 Bi-directional (Standard)
Calibration	Automatic External
Display	Backlit display with 25mm high digits and capacity tracker
Power supply	Mains Power Cord / 6v 4Ah battery
Operating temperature	-10°C to 40°C
Housing	Indicator: ABS Plastic, Top Pan: Grade 304 stainless steel, Base: Aluminum
Overall dimensions (wxdxh)	400mm x 620mm x 860mm (only GFK 75, 150, 300 and GFK-M models) GFK 600: 600mm x 940mm x 900mm
Net weight	12.46kg (GFK 600-25.5kg)

Accessories

No.700000012 Adam printer
 No.3074010266 RS-232 cable
 No.3074010507 RS-232 to USB Interface Cable
 (must be ordered with No. 3074010266 RS-232 cable)
 No.3052010526 In-use cover
 No.400005054 Thermal printer paper
 No.600002028 AdamDU - Data Collection Program

Features

- Full tare range
- Accessible internal Rechargeable Battery
- Large backlit LCD display with capacity tracker
- Battery operation with auto-off to save battery life
- Parts counting with freely selectable sample sizes
- Check weighing LED lights to show acceptable limits
- Automatic memory accumulation
- Bi-directional RS-232 output for connection to computers and printers
- Grade 304 stainless steel pan

Applications

- Weighing
- Check weighing
- Percentage weighing
- Dynamic/Animal weighing
- Parts Counting

